



ITEM: BLOUSE, FEMALE SWORN MEMBERS - PRESCRIBED

MATERIAL: Style #1113, medium weight, Brawny Blue, 14 oz
Style #460-96, Raeford Worsted, 14 oz.
Style #386-14, P&F, Metcalf Bros. 14 oz.

CONSTRUCTION: Shall be woman's style single-breasted, four button, straight front (no button stand), peak lapels, semi-drape front and semi-fitted back. Four plain patch pockets with scalloped flaps to button. Coat length to extend to just below the buttocks. Officer's coats are to have shoulder straps of same material.

Lapels and Collar: Lapels to be 7- $\frac{1}{2}$ " to 8" long or outside edge to top buttonhole, and to be 4" from point to breakline, and notch to be 2- $\frac{1}{2}$ " deep.

Collar to be 1- $\frac{3}{4}$ " wide at center of back, and 3- $\frac{1}{2}$ " from edge of breakline and 1- $\frac{1}{2}$ " from notch to edge. Blue wool undercollar cloth. Collar stand to be 1- $\frac{1}{8}$ " wide to be substantially stitched for firmness.

Outside Pocket: Two upper breast pockets, blind patch, to be 5" x 6" long from top to flap to bottom of patch. A three-pointed scalloped flap to button, and stitched down at sides. Flaps to be 2" from top to points. Top of pocket should be on a line with top button of coat to be placed on a straight line with edge of coat, 3- $\frac{3}{4}$ " from finished edge. Two lower pockets, plain blind patch to be 6" wide x 8" long from top of flap to bottom of patch. A three pointed scalloped flap to button at center, and stitched down at sides. Flaps to measure 3" from top to points.

Top of pocket to be on a line with lower button, and to be placed on a straight line with edge of coat 4- $\frac{1}{2}$ " from finished edge.

Inside Pockets: Two horizontal upper breast pockets 6" x 7" deep. Top of pockets to be placed approximately midway between top and second button.

Lower cash pocket on left side to be 4- $\frac{1}{2}$ " wide by 5" deep.

Pocketing: All pockets to be of #2.50 heavy drill, 72 x 60 count.

Body Lining: One-half lined with yoke and sleeves to be of 120 count dark rayon lining. Reinforcement on both foreparts sewn over lining of C.M. London Co. #6000 to extend from facing to side seams, 8- $\frac{1}{2}$ " wide to be placed 3- $\frac{1}{2}$ " below armhole line. Bottom lining to be sewn down all around.



ITEM: BLOUSE, FEMALE SWORN MEMBERS - PRESCRIBED

CONSTRUCTION:
(Continued)

Arm Shields: To be made of same material as coat, piped and machine sewn to lining.

Facing: Inside facing shall be of same material as coat, cut in one piece and shall not be less than 6" at the top and tapering to not less than 3-1/2" at the bottom.

Side Vents: To have two side vents in side seams, not less than 7" nor more than 8" long and to be fastened with two snaps on each side.

Buttons: Four buttons to be placed on left side of coat, 1-1/2" from finished edge. Buttons to be spaced vertically equidistant 3-1/2" apart. Buttons to be securely sewn through and reinforced from inside with eighteen ligne black buttons.

Buttonholes: To be Reese machined buttonholes 1/2" from finished edge. No buttonholes in lapels.

Sleeves: Two buttons, twenty-six ligne CPD, sunk near back seam at wrist, first button to be 2" from bottom edge and second button to be 1-1/4" apart. No stitching on sleeves.

Edges: Single stitched 1/4" collar front edge, pockets and flaps

Seams: All seams plain.

Nameplate Patch: Two round eyelets, spaced 1-5/8" apart. To be placed 1/4" above the top seam of the pocket flap on the right breast and centered. Reinforcement of same material will be sewn on the outside and will not exceed 2-1/4" x 1/2". The thread for the eyelets will be of the same color and colorfast.

Star Patch: Cut from blue broadcloth, rectangular in shape, with two metal eyelets. Patch shall be 2" in length and 7/8" wide. Distance between center of eyelets shall be 1-1/4".

Star patches shall be placed on left breast. Bottom of star patch to be 3/4" above top edge of pocket, and eyelets centered with buttons.

Shoulder Straps for Lieutenant and Above: To be of same material as coat, 2-1/4" wide at shoulder seam, extending under the collar to measure 1-3/4" at edge of collar. One twenty-four ligne CPD button to be sunk through shoulder strap at the edge of collar and sewed to shoulder.



ITEM: BLOUSE, FEMALE SWORN MEMBERS - PRESCRIBED

CONSTRUCTION: City of Chicago Flag Shoulder Patch: Patch to be sewn on the
(Continued) right shoulder, centered 1-1/4" below the outer shoulder seam.

Shoulder Patch: The specified shoulder patch will be sewn on
the left sleeve, 3/4" down from the shoulder seam.

Maker's Specification Guarantee/Identification Tag: This tag
is furnished by the Department and will be sewn inside the right
inside pocket by the manufacturer or uniform house.

In all areas not specifically covered by this specification, the
garment will conform to the standard sample which may be seen at
the Chicago Police Department, Research and Development Division

Authenticated by:

ggc

Fred Rice
Superintendent of Police