



ITEM: TROUSERS, WOOL, MALE AND FEMALE - PRESCRIBED

MATERIAL: #460-96, Raeford Worsted, 14 oz.
#386-14, Metcalf Bros., 14 oz.

CONSTRUCTION: Prescribed police trousers with two side, two hip and one watch pocket. Plain buttons, belt loops, suspender buttons.

Pockets: To have two side on-seam pockets, with outside opening to measure 7", to measure not less on the inside from bottom of band to bottom of pocket, 11" deep. To have two hip pockets to be finished 6-1/2" wide and 7-1/2" deep, inside measure. One watch pocket set on the right side in the waistband seam.

Pocketing: All pockets to be of #2.50 heavy drill 72 x 60 count.

Seams: For all ranks to be plain.

Fly: Zipper

Belt Loops: Trousers to be equipped with seven belt loops, 1" wide 2" deep sewn in the waistband seam.

Waistband: To be 2" wide when finished and the waistband lining is to be made with Snugtex, to prevent shirt from coming out of trousers, fastened in front with the Hookflex Hook and Eye, a stapled-in product which is supported by a backplate for both the hook and eye. The hook and eye is to be made of rust-resistant steel.

Bottoms: Plain bottom trouser, finished with cloth heel reinforcement.

Special Instructions to Cutter: The finished length of the trouser, is to be cut so that the front edge of the trouser touches the shoe in a straight line. The finished width of the trouser must not be less than 16" wide nor more than 19" wide.

Crotch Lining: The crotch to be lined with linen or cotton material and to be stay-taped.

Outlets: There is to be a 2" outlet at the waist, and a 2" turnup at the bottom.

Maker's Specification Guarantee/Identification Tag: This tag furnished by the Chicago Police Department will be sewn on the underside of the right hip pocket, or inside front of the waistband on the right side, or inside the back right or left pocket by the manufacturer or uniform house.

Authenticated by:

Fred Rice
Superintendent of Police